

GAS FURNACES

R95T FEATURES

Rheem *Classic® Plus Series* multi position Gas Furnaces



- 95% AFUE
- Input Rates from 40 to 115 kBTU.

Limited Warranty

- Conditional Parts (Registration Required) - Ten (10) Years
- Heat Exchanger - Limited Lifetime

95% residential gas furnace CSA certified

- 4 way multi-prise design
- PlusOne™* Diagnostics 7-Segment LED on all units
- PlusOne™* Ignition System - DSI for reliability and longevity
- PlusOne™* Water Management System with patent pending Blocked Drain Sensor
- Heat exchanger is removable for improved serviceability. Aluminized steel primary and stainless steel secondary construction provide maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" cabinet ideal for space constrained installations.
- Blower Shelf design - serviceable in all furnace orientations.
- Pre marked hoses - insures proper system drainage
- Vent with 2" or 3" PVC
- Replaceable Collector Box
- Hemmed edges on cabinet and doors.
- Constant Torque electrically commutated motor.
- Quarter turn fasteners for tool less access
- Integrated control boards feature dip switches for easy system set up.
- Self priming condensate trap
- Solid bottom included.

Model	Input BTU/Hr	Output BTU/Hr	Cooling (CFM)	Height Inches [mm]	Length Inches [mm]	Width Inches [mm]	Weight lbs [kg]	AFUE	Motor
R95TA0401317MSA	42000	39900		34	29-5/8	17-1/2	113.0	95.00	Constant Torque
R95TA0601317MSA	56000	53200		34	29-5/8	17-1/2	118.0	95.00	Constant Torque
R95TA0701317MSA	70000	66500		34	29-5/8	17-1/2	122.0	95.00	Constant Torque
R95TA0701521MSA	70000	66500		34	29-5/8	21		95.00	Constant Torque
R95TA0851521MSA	84000	79800		34	29-5/8	21	136.0	95.00	Constant Torque
R95TA1001521MSA	98000	93100		34	29-5/8	21	141.0	95.00	Constant Torque

GAS FURNACES

R95T

Model	Input BTU/Hr	Output BTU/Hr	Cooling (CFM)	Height Inches [mm]	Length Inches [mm]	Width Inches [mm]	Weight lbs [kg]	AFUE	Motor
R95TA1151524MSA	112000	106400		34	29-5/8	24-1/2	152.0	95.00	Constant Torque
R95TB0851521MSA	84000	79800		34	29-5/8	21	136.0	95.00	Constant Torque
R95TC0401317MSA	42000	39900	1200	34	29-5/8	17-1/2	113.0	95.00	Constant Torque
R95TC0601317MSA	56000	53200	1250	34	29-5/8	17-1/2	118.0	95.00	Constant Torque
R95TC0701317MSA	70000	66500	1250	34	29-5/8	17-1/2	122.0	95.00	Constant Torque
R95TC0701521MSA	70000	66500		34	29-5/8	21		95.00	Constant Torque
R95TC0851521MSA	84000	79800	1850	34	29-5/8	21	136.0	95.00	Constant Torque
R95TC1001521MSA	98000	93100	1925	34	29-5/8	21	141.0	95.00	Constant Torque
R95TC1151524MSA	112000	106400	1750	34	29-5/8	24-1/2	152.0	95.00	Constant Torque
R95TX851521MSA	84000	79800		34	29-5/8	21		95.00	Constant Torque